

2 way flow reg. screw-in valve (adjustable)

FR2-16.-.-0-.....

Ordering example:

FR2 - 16N - C - 0 - 03.00

A B C D E



IMAV-Hydraulik GmbH
Breite Strasse 10
D-40670 Meerbusch (Osterath)
Phone +49 (0)2159 - 9188.0
Fax +49 (0)2159 - 4242
E-mail: info@imav.com
Internet: <http://www.imav.com>

MF-140-160-00

(Subject to change!)

Model code:

- A design**
flow regulator valve
- B size and sealing**
16N = Buna (NBR)
16V = Viton (FPM)
- C adjustment**
S = screw adjustment
C = cap
K = handknob
- D construction**
0 = screw-in valve

- E quantity adjustment**
requested regulated flow
Q specify in gpm
1 l/min = 0.265 Gpm
(1 Gpm = 3.785 l/min)
regulation tolerance
2.0 - 11.0 l/min $\pm 15\%$
11.0 - 114.0 l/min $\pm 10\%$

Technical Data:

note:	max. 50% volumen-reduction of the factory set flow
nominal pressure:	210 bar
nominal flow:	114 l/min
weight:	0.71 kg
temperature range:	-40°C to 120°C
fluids:	hydraulic oil as per DIN 51524 T1 (ISO TC 131)
seals:	optional Buna (NBR) or Viton (FPM), as well as Teflon wascher (PTFE)
cavity:	C-16-2 see datasheet no. IK-100-169-00
housing:	2LH-16.-B.. see datasheet no. IH-100-000-00
seal kit:	SP-MDS-16N-21 (NBR), SP-MDS-16V-21 (FPM)