


dvograni uvrtni regulator protoka (podesivi)

FR2-16.-.-0-.....

Primjer za porudzbu

FR2 - 16N - C - 0 - 03.00



IMAV-Hydraulik GmbH
Breite Strasse 10
D-40670 Meerbusch (Osterath)
Telefon +49 (0)2159 - 9188.0
Telefax +49 (0)2159 - 4242
E-mail: info@imav.com
Internet: <http://www.imav.com>

MF-140-160-00

(Promjene nisu isključene!)

Kljuc

- | | |
|---|---|
| <p>A izvedba
regulator protoka</p> <p>B velicina i zaptivac
16N = Buna (NBR)
16V = viton (FPM)</p> <p>C vrsta podesavanja
S = vreteno sa zavojnicom
C = cep
K = rucni tocak</p> <p>D konstrukcija
0 = uvrtni ventil</p> | <p>E podesavnje protoka
zeljeni regulirani protok ulja
Q naznaceni u gpm
1 l/min = 0,265 Gpm
(1 Gpm = 3,785 l/min)
tolerancija regulacije
2,0 - 11,0 l/min ±15%
11,0 - 114,0 l/min ±10%</p> |
|---|---|

Tehnicke informacije

uputa:	max. 50% reduciranje fabrički određenog volumena
nazivni pritisak:	210 bar
nazivni protok:	114 l/min
težina:	0,71 kg
područje temperature:	-40°C do 120°C
medium:	hidraulično ulje po DIN 51524 T1 (ISO TC 131)
opcija:	opcionalno Buna (NBR) ili Viton (FPM), kao i teflon metalni prsten (PTFE)
uvrtina:	C-16-2 vidi stranicu broj: IK-100-169-00
kuciste:	2LH-16.-B.. vidi stranicu broj: IH-100-000-00
komplet zaptivaca:	SP-MDS-16N-21 (NBR), SP-MDS-16V-21 (FPM)